




TRITON
CDS



T3CDSPB

Ex e Exd Ex nR Ex ta

Triton CDS PB (T3CDSPB) Globally Approved, Explosive Atmosphere Cable Gland

For all types of Lead Sheathed Armoured Cables

- Effectively earths / grounds lead sheathed cables
- Fully sequential, three step installation procedure
- Direct & remote installation
- Unique compensating displacement seal system (CDS)
 - Metal-to-metal installation every time regardless of lead sheath diameter
- Designed to prevent Coldflow, see CMP Technical Document TS002
- Integral protected deluge seal
- Controlled outer 'load retention' seal
- Unique OSTG prevents overtightening
- 60°C to +130°C
- Globally marked, IECEx & ATEX
- Superior EMC performance



† Grooved Cone (X) is predominantly used for Wire Braid (e.g. GSWB, TCWB), Steel Tape Armour (STA, DSTA) and Aluminium Strip Armour (ASA) but is also suitable for Single Wire Armour (SWA), Aluminium Wire Armour (AWA) and Pliable Wire Armour (PWA) if the range is outside that of the Stepped Cone (W).

Grooved Cone (X) dimensions shown in the Cable Gland Selection Table below are for a double wire strand of braid armoured cables. Tapes can also be doubled over. For cables that have only a single layer of armour such as SWA the clamping range should be used as shown in the table below.

Stepped (W) Cone is suitable for Single Wire Armour (SWA), or Aluminium Wire Armour (AWA) cables.

TECHNICAL DATA

Design Specification	BS 6121:Part 1:1989, IEC 62444, EN 62444
Mechanical Classification*	Impact = Level 8, Cable Anchorage = Class D
Enclosure Protection	IK10 to IEC 62262 (20 joules) Brass & Stainless Steel only
Electrical Classification*	Category B (Category A when used with braid, tape or pliable wire armour cables)
ATEX Certificate	CML 18ATEX1326X, CML 18ATEX4318X
Code of Protection	⊕ II 2G, II 1D, Ex db IIC Gb, Ex eb IIC Gb, Ex ta IIIC Da, ⊕ II 3G Ex nR IIC Gc, ⊕ I M2, Ex db I Mb, Ex eb I Mb
Compliance Standards	EN 60079-0,1,7,15,31
IECEx Certificate	IECEx CML 18.0183X, IECEx SIM 14.0007X
Code of Protection	Ex db IIC Gb, Ex eb IIC Gb, Ex nR IIC Gc, Ex ta IIIC Da, Ex db I Mb, Ex eb I Mb
Compliance Standards	IEC 60079-0,1,7,15,31
EAC Certificate	TC RU C-GB.AA87.B.00487
UkrSEPRO	UA.TR.047.C.0644-15
NEPSI Certificate	GYJ18.1253X
CCOE / PESO (India) Certificate	P333688
INMETRO Approval	TUV 11.0374X
RETIE Approval	03866
Marine Approvals	LRS: 01/00172, DNV: TAE000000Y, ABS: 14-LD234401A-4-PDA, BV: 43180 A1 BV
Ingress Protection Rating**	IP66, IP67 & IP68***
Deluge Protection Compliance	DT501 : 91
Cable Gland Material	Brass, Electroless Nickel Plated Brass, Aluminium, Stainless Steel
Seal Material	CMP SOLO LSF Halogen Free Thermoset Elastomer
Cable Type	Lead Sheathed & Single Wire Armour (LC/SWA), Lead Sheathed & Aluminium Wire Armour (LC/AWA), Lead Sheathed & Wire Braid Armour (LC/SWB), Lead Sheathed & Pliable Wire Armour (LC/PWA), Lead Sheathed & Steel Tape Armour (LC/STA), Lead Sheathed & Aluminium Strip Armour (LC/ASA)
Armour Clamping	Reversible Armour Cone & AnyWay Universal Clamping Ring
Sealing Technique	Inner Bedding Sealing Ring: Compensating Displacement Seal (CDS), Outer Sheath Sealing Ring : Load Retention Seal (LRS)
Sealing Area(s)	Cable Inner Lead Covering & Cable Outer Sheath

* Mechanical & Electrical Classifications applied as per IEC 62444 & EN 62444
 ** When CMP installation accessories are used. Refer to page 7 or www.cmp-products.com for further information.
 *** IP68 tested to a minimum depth of 30 metres for 12 hours, alternate depths / durations can be provided upon request

Cable Gland Selection Table

Refer to illustration at the top of the page.

Dimensions listed below are for metric cable glands only
 Dimensions for alternative threads may vary, please see supplementary technical data sheet

Cable Gland Size	Available Entry Threads "C" (Alternate Metric Thread Lengths Available)				Lead Sheath Diameter "A"		Overall Cable Diameter "B"		Armour Range †				Across Flats "D"	Across Corners "D"	Protrusion Length "F"	Combined Ordering Reference (*Brass Metric)			Shroud	Cable Gland Weight (Kgs)	
	Standard		Option		Min	Max	Min	Max	Grooved Cone (X)		Stepped Cone (W)					Size	Type	Ordering Suffix			
	Metric	Thread Length (Metric) "E"	NPT	Thread Length (NPT) "E"					NPT	Min	Max	Min	Max	Min	Max				Min	Max	
20S16	M20	15.0	1/2"	19.9	3/4"	3.1	7.8	6.1	13.1	0.3	1.0	0.8	1.25	24.0	26.4	78.7	20S16	T3CDSPB	1RA	PVC36	0.20
20S	M20	15.0	1/2"	19.9	3/4"	6.1	11.0	9.5	15.9	0.3	1.0	0.8	1.25	24.0	26.4	78.7	20S	T3CDSPB	1RA	PVC36	0.20
20	M20	15.0	1/2"	19.9	3/4"	6.5	13.4	12.5	20.9	0.4	1.0	0.8	1.25	30.5	33.6	76.2	20	T3CDSPB	1RA	PVC06	0.28
25S	M25	15.0	3/4"	20.2	1"	11.1	19.3	14.0	22.0	0.4	1.2	1.25	1.6	37.5	41.3	88.8	25S	T3CDSPB	1RA	PVC09	0.44
25	M25	15.0	3/4"	20.2	1"	11.1	19.3	18.2	26.2	0.4	1.2	1.25	1.6	37.5	41.3	88.7	25	T3CDSPB	1RA	PVC09	0.44
32	M32	15.0	1"	25.0	1 1/4"	17.0	25.5	23.7	33.9	0.4	1.2	1.6	2.0	46.0	50.6	90.7	32	T3CDSPB	1RA	PVC11	0.64
40	M40	15.0	1 1/4"	25.6	1 1/2"	22.0	31.2	27.9	40.4	0.4	1.6	1.6	2.0	55.0	60.5	93.2	40	T3CDSPB	1RA	PVC15	0.91
50S	M50	15.0	1 1/2"	26.1	2"	29.5	37.2	35.2	46.7	0.4	1.6	2.0	2.5	60.0	66.0	100.7	50S	T3CDSPB	1RA	PVC18	1.13
50	M50	15.0	2"	26.9	2 1/2"	35.6	42.6	40.4	53.0	0.6	1.6	2.0	2.5	70.1	77.1	105.8	50	T3CDSPB	1RA	PVC21	1.61
63S	M63	15.0	2"	26.9	2 1/2"	40.1	48.5	45.6	59.4	0.6	1.6	2.0	2.5	75.0	82.5	102.5	63S	T3CDSPB	1RA	PVC23	1.74
63	M63	15.0	2 1/2"	39.9	3"	47.2	54.2	54.6	65.8	0.6	1.6	2.0	2.5	80.0	88.0	105.4	63	T3CDSPB	1RA	PVC25	1.79
75S	M75	15.0	2 1/2"	39.9	3"	52.8	60.2	59.0	72.0	0.6	1.6	2.0	2.5	90.0	99.0	110.6	75S	T3CDSPB	1RA	PVC28	2.58
75	M75	15.0	3"	41.5	3 1/2"	59.1	65.2	66.7	78.4	0.6	1.6	2.5	3.0	100.0	110.0	120.3	75	T3CDSPB	1RA	PVC30	3.34
90	M90	24.0	3 1/2"	42.8	4"	66.6	77.1	76.2	90.3	0.8	1.6	3.15	4.0	115.0	126.5	138.9	90	T3CDSPB	1RA	PVC32	4.89
100	M100	24.0	3 1/2"	42.8	4"	76.0	88.1	86.1	101.4	0.8	1.6	3.15	4.0	127.0	139.7	128.2	100	T3CDSPB	1RA	LSF33	4.99
115	M115	24.0	4"	44.0	5"	86.0	94.1	101.5	110.2	0.8	1.6	3.15	4.0	138.0	151.8	161.3	115	T3CDSPB	1RA	LSF34	7.75
130	M130	24.0	5"	46.8	-	97.0	110.1	110.2	123.2	0.8	1.6	3.15	4.0	157.0	172.7	173.3	130	T3CDSPB	1RA	LSF35	9.81

*For material options add the following suffix to the Ordering Reference, Brass (no suffix required); Nickel Plated Brass 'S'; 316 Grade Stainless Steel '4'; Copper Free Aluminium '1'. For NPT options add the following digits to the material suffix; 1/2" = 31; 3/4" = 32; 1" = 33; 1 1/4" = 34; 1 1/2" = 35; 2" = 36; 2 1/2" = 37; 3" = 38; 3 1/2" = 39; 4" = 310 (Brass requires prefix '0')

Examples: 32T3CDSPB1RA534 = Nickel Plated Brass 1 1/4" NPT, 50S13CDSPB1RA035 = Brass 1 1/2" NPT, 25T3CDSPB1RA432 = Stainless Steel 3/4" NPT, 20T3CDSPB1RA5 = Nickel Plated Brass M20

Dimensions are displayed in millimetres unless otherwise stated