


717 Ex e

717 NYLON UNIVERSAL STOPPER PLUG, EXPLOSIVE ATMOSPHERE Ex e CABLE / CONDUIT ACCESSORY

- Provides means of blanking unused cable entries
- Cost effective moulded design
- Universal tightening design (hex head, allen key and slotted/flat screw head)
- Temporary or permanent
- Ex e black or blue only
- Equipment interface seal available
- -60 to +95°C



COLOUR	SUFFIX	METRIC ORDERING EXAMPLE	NPT ORDERING EXAMPLE
BLACK - RAL9011	-	717EM2	717ET1
BLUE - RAL5015	4	717EM24	717ET14

TECHNICAL CLASSIFICATION	
INGRESS PROTECTION RATING	*MINIMUM IP68 DEPTH AND DURATION
WITHOUT ENTRY THREAD SEAL FITTED	IP66,IP67,IP68*,IP69,IP69K 1.1 metres for 16 hours**
WITH ENTRY THREAD SEAL FITTED	IP66,IP67,IP68*,IP69,IP69K 30 metres for 16 hours**
AVAILABLE MATERIALS	Nylon only
CONTINUOUS OPERATING TEMPERATURE	Ex e -60°C to +95°C

GLOBAL PRODUCT CERTIFICATION			
ATEX CERTIFICATE	CML20ATEX3054X	IECEx CERTIFICATE	IECEx CML 20.0038X
CODE OF PROTECTION	Ⓔ II 2GTD Ex eb IIC Gb, Ex ta IIIC Da	CODE OF PROTECTION	Ex eb IIC Gb, Ex ta IIIC Da
COMPLIANCE STANDARDS	EN 60079-0, 7, 31	COMPLIANCE STANDARDS	IEC 60079-0, 7, 31

**Alternate depths / durations can be provided upon request.

STOPPER PLUG RANGE			
In addition to the 717, CMP offers a wide range of stopper plugs suitable for Ex e and Ex d environments, manufactured from metallic or polymer material. Please refer to our website or full product catalogue.			
717 Universal Stopper Plug (Shown here)	747 Recessed Stopper Plug	757 Hexagon Head Stopper Plug	767 Dome Head Stopper Plug

PRODUCT SELECTION TABLE - METRIC					
ORDERING REFERENCE	THREAD SIZE	MINIMUM THREAD LENGTH	ACROSS FLATS	ACROSS CORNERS DIAMETER	PROTRUSION LENGTH
717EM2	M20	10.0	24.0	26.3	7.0
717EM3	M25	10.0	28.0	30.7	7.0
717EM4	M32	10.0	38.0	41.7	8.0
All dimensions shown are in millimetres unless otherwise stated					

Ordering reference shown for black metric product

PRODUCT SELECTION TABLE - NPT					
ORDERING REFERENCE	THREAD SIZE	MINIMUM THREAD LENGTH	ACROSS FLATS	ACROSS CORNERS DIAMETER	PROTRUSION LENGTH
717ET1	½"	14.0	24.0	26.3	7.0
717ET2	¾"	14.0	28.0	30.7	7.0
717ET3	1"	14.0	38.0	41.7	8.0
All dimensions shown are in millimetres unless otherwise stated					

Ordering reference shown for black imperial product