



- For safely running cables into Ex e and Ex i areas
- Can be used in a temperature range from -60 to +75 °C, degree of protection IP68
- Available in Ex e and Ex i versions; the Ex i version is identified by a blue cap nut
- Cable dia. ranges from 1 to 48 mm
- Versions with multi-seal inserts

E10

MY R. STAHL 8161B



R. STAHL's Series 8161/7 and 8161/8 cable glands can be used to safely run cables into Ex e enclosures. They are suitable for cable diameters between 1 and 48 mm. They are available for Ex e and Ex i electrical circuits – the Ex i version can be distinguished by its blue cap nut. A stopping plug for unused entries can be integrated into the entries.

	IECEx / ATEX					
Zone	0	1	2	20	21	22
Installation in		•	•		•	•

Selection Table										
Product description Ambient temperature Variant Ex version				Cable gland For low temperature With reduction sealing insert -60 °C ... +75 °C Low temperature Ex e						
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M20	4 – 13 mm	24 mm	27 mm	10 mm	36 ... 43 mm	Black	50	8161/7-M20-1304-LT	329692	13 g
M25	7 – 17 mm	29 mm	32 mm	10 mm	38 ... 46 mm	Black	50	8161/7-M25-1707-LT	329693	19 g
M32	9 – 21 mm	36 mm	40 mm	12 mm	42 ... 50 mm	Black	25	8161/7-M32-2109-LT	329694	32 g
M40	12 – 28 mm	46 mm	51 mm	12 mm	52 ... 65 mm	Black	10	8161/7-M40-2812-LT	340446	68 g
M50	16 – 35 mm	55 mm	61 mm	14 mm	59 ... 72 mm	Black	4	8161/7-M50-3516-LT	340447	107 g
M63	28 – 48 mm	68 mm	75 mm	15 mm	64 ... 78 mm	Black	1	8161/7-M63-4828-LT	340448	155 g
Product description Ambient temperature Variant Ex version				Cable gland For low temperature With reduction sealing insert -60 °C ... +75 °C Low temperature Ex i						
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M20	4 – 13 mm	24 mm	27 mm	10 mm	36 ... 43 mm	Blue	50	8161/8-M20-1304-LT	329696	13 g
M25	7 – 17 mm	29 mm	32 mm	10 mm	38 ... 46 mm	Blue	50	8161/8-M25-1707-LT	329697	19 g
M32	9 – 21 mm	36 mm	40 mm	12 mm	42 ... 50 mm	Blue	25	8161/8-M32-2109-LT	329698	32 g

Selection Table

Product description		Cable gland For low temperature With reduction sealing insert								
Ambient temperature		-60 °C ... +75 °C								
Variant		Low temperature								
Ex version		Ex i								
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M40	12 – 28 mm	46 mm	51 mm	12 mm	52 ... 65 mm	Blue	10	8161/8-M40-2812-LT	340449	68 g
M50	16 – 35 mm	55 mm	61 mm	14 mm	59 ... 72 mm	Blue	4	8161/8-M50-3516-LT	340450	107 g
M63	28 – 48 mm	68 mm	75 mm	15 mm	64 ... 78 mm	Blue	1	8161/8-M63-4828-LT	340481	155 g
Product description		Cable gland For low temperature With reduction sealing insert								
Ambient temperature		-40 °C ... +75 °C								
Variant		Low temperature								
Ex version		Ex e								
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M16	2 – 9 mm	20 mm	22 mm	9 mm	31 ... 37 mm	Black	50	8161/7-M16-0902-LT	329691	9 g
Product description		Cable gland For low temperature With reduction sealing insert								
Ambient temperature		-40 °C ... +75 °C								
Variant		Low temperature								
Ex version		Ex i								
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M16	2 – 9 mm	20 mm	22 mm	9 mm	31 ... 37 mm	Blue	50	8161/8-M16-0902-LT	329695	9 g
Product description		Cable gland with multiple sealing insert Black								
Number of cables		4								
Ambient temperature		-40 °C ... +75 °C								
Ex version		Ex e								
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M25	3.2 – 3.5 mm	29 mm	32 mm	10 mm	38 to 46 mm	Black	50	8161/7-M25-9999-MFD-04035	265083	20 g
Product description		Cable gland with multiple sealing insert Black								
Number of cables		4								
Ambient temperature		-40 °C ... +75 °C								
Ex version		Ex i								
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M25	3.2 – 3.5 mm	29 mm	32 mm	10 mm	38 to 46 mm	Blue	50	8161/8-M25-9999-MFD-04035	265084	20 g
Product description		Cable gland with multiple sealing insert Green								
Number of cables		4								
Ambient temperature		-40 °C ... +75 °C								
Ex version		Ex e								
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M25	4.1 – 4.5 mm	29 mm	32 mm	10 mm	38 to 46 mm	Black	50	8161/7-M25-9999-MFD-04045	265085	10 g
Product description		Cable gland with multiple sealing insert Green								
Number of cables		4								
Ambient temperature		-40 °C ... +75 °C								
Ex version		Ex i								
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M25	4.1 – 4.5 mm	29 mm	32 mm	10 mm	38 to 46 mm	Blue	50	8161/8-M25-9999-MFD-04045	265086	20 g

Selection Table										
Product description Number of cables Ambient temperature Ex version				Cable gland with multiple sealing insert Red 4 -40 °C ... +75 °C Ex e						
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M25	4.7 – 5.2 mm	29 mm	32 mm	10 mm	38 to 46 mm	Black	50	8161/7-M25-9999-MFD-04052	265087	20 g
M32	4.5 – 5 mm	36 mm	40 mm	12 mm	42 to 50 mm	Black	25	8161/7-M32-9999-MFD-04050	265089	36 g
Product description Number of cables Ambient temperature Ex version				Cable gland with multiple sealing insert Red 4 -40 °C ... +75 °C Ex i						
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M25	4.7 – 5.2 mm	29 mm	32 mm	10 mm	38 to 46 mm	Blue	50	8161/8-M25-9999-MFD-04052	265088	20 g
M32	4.5 – 5 mm	36 mm	40 mm	12 mm	42 to 50 mm	Blue	25	8161/8-M32-9999-MFD-04050	265090	36 g
Product description Number of cables Ambient temperature Ex version				Cable gland with multiple sealing insert White 4 -40 °C ... +75 °C Ex e						
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M25	3.6 – 4 mm	29 mm	32 mm	10 mm	38 to 46 mm	Black	50	8161/7-M25-9999-MFD-04040	261983	20 g
M25	5.4 – 6 mm	29 mm	32 mm	10 mm	38 to 46 mm	Black	50	8161/7-M25-9999-MFD-04060	261981	20 g
M32	6.3 – 7 mm	36 mm	40 mm	12 mm	42 to 50 mm	Black	25	8161/7-M32-9999-MFD-04070	265091	36 g
Product description Number of cables Ambient temperature Ex version				Cable gland with multiple sealing insert White 4 -40 °C ... +75 °C Ex i						
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M25	3.6 – 4 mm	29 mm	32 mm	10 mm	38 to 46 mm	Blue	50	8161/8-M25-9999-MFD-04040	261984	20 g
M25	5.4 – 6 mm	29 mm	32 mm	10 mm	38 to 46 mm	Blue	50	8161/8-M25-9999-MFD-04060	261982	20 g
M32	6.3 – 7 mm	36 mm	40 mm	12 mm	42 to 50 mm	Blue	25	8161/8-M32-9999-MFD-04070	265092	36 g
Product description Ambient temperature Variant Ex version				Cable gland With reduction sealing insert -40 °C ... +75 °C Long thread Ex e						
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M16	2 – 9 mm	20 mm	22 mm	15 mm	37 to 43 mm	Black	50	8161/7-M16-0902-L	239187	9 g
M20	4 – 13 mm	24 mm	27 mm	15 mm	41 to 48 mm	Black	50	8161/7-M20-1304-L	239188	13 g
M25	7 – 17 mm	29 mm	32 mm	15 mm	43 to 51 mm	Black	50	8161/7-M25-1707-L	239189	19 g

Selection Table

Product description Ambient temperature Variant Ex version		Cable gland With reduction sealing insert -40 °C ... +75 °C Long thread Ex e								
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M32	9 – 21 mm	36 mm	40 mm	15 mm	45 to 53 mm	Black	25	8161/7-M32-2109-L	239190	32 g
M40	12 – 28 mm	46 mm	51 mm	18 mm	58 to 71 mm	Black	10	8161/7-M40-2812-L	239191	68 g
M50	16 – 35 mm	55 mm	61 mm	18 mm	63 to 76 mm	Black	4	8161/7-M50-3516-L	239192	107 g
M63	28 – 48 mm	68 mm	75 mm	18 mm	67 to 81 mm	Black	1	8161/7-M63-4828-L	239193	155 g
Product description Ambient temperature Variant Ex version		Cable gland With reduction sealing insert -40 °C ... +75 °C Long thread Ex i								
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M16	2 – 9 mm	20 mm	22 mm	15 mm	37 to 43 mm	Blue	50	8161/8-M16-0902-L	239195	9 g
M20	4 – 13 mm	24 mm	27 mm	15 mm	41 to 48 mm	Blue	50	8161/8-M20-1304-L	239196	13 g
M25	7 – 17 mm	29 mm	32 mm	15 mm	43 to 51 mm	Blue	50	8161/8-M25-1707-L	239197	19 g
M32	9 – 21 mm	36 mm	40 mm	15 mm	45 to 53 mm	Blue	25	8161/8-M32-2109-L	239198	32 g
M40	12 – 28 mm	46 mm	51 mm	18 mm	58 to 71 mm	Blue	10	8161/8-M40-2812-L	239199	68 g
M50	16 – 35 mm	55 mm	61 mm	18 mm	63 to 76 mm	Blue	4	8161/8-M50-3516-L	239200	107 g
M63	28 – 48 mm	68 mm	75 mm	18 mm	67 to 81 mm	Blue	1	8161/8-M63-4828-L	239201	155 g
Product description Ambient temperature Variant Ex version		Cable gland With reduction sealing insert -40 °C ... +75 °C Standard thread Ex e								
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M16	2 – 9 mm	20 mm	22 mm	9 mm	31 to 37 mm	Black	50	8161/7-M16-0902	239155	9 g
M20	4 – 13 mm	24 mm	27 mm	10 mm	36 to 43 mm	Black	50	8161/7-M20-1304	239156	10 g
M25	7 – 17 mm	29 mm	32 mm	10 mm	38 to 46 mm	Black	50	8161/7-M25-1707	239157	10 g
M32	9 – 21 mm	36 mm	40 mm	12 mm	42 to 50 mm	Black	25	8161/7-M32-2109	239158	32 g
M40	12 – 28 mm	46 mm	51 mm	12 mm	52 to 65 mm	Black	10	8161/7-M40-2812	239159	68 g
M50	16 – 35 mm	55 mm	61 mm	14 mm	59 to 72 mm	Black	4	8161/7-M50-3516	239160	107 g
M63	28 – 48 mm	68 mm	75 mm	15 mm	64 to 78 mm	Black	1	8161/7-M63-4828	239161	155 g
Product description Ambient temperature Variant Ex version		Cable gland With reduction sealing insert -40 °C ... +75 °C Standard thread Ex i								
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M16	2 – 9 mm	20 mm	22 mm	9 mm	31 to 37 mm	Blue	50	8161/8-M16-0902	239163	9 g

Selection Table										
Product description Ambient temperature Variant Ex version			Cable gland With reduction sealing insert -40 °C ... +75 °C Standard thread Ex i							
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M20	4 – 13 mm	24 mm	27 mm	10 mm	36 to 43 mm	Blue	50	8161/8-M20-1304	239164	10 g
M25	7 – 17 mm	29 mm	32 mm	10 mm	38 to 46 mm	Blue	50	8161/8-M25-1707	239165	19 g
M32	9 – 21 mm	36 mm	40 mm	12 mm	42 to 50 mm	Blue	25	8161/8-M32-2109	239166	32 g
M40	12 – 28 mm	46 mm	51 mm	12 mm	52 to 65 mm	Blue	10	8161/8-M40-2812	239167	68 g
M50	16 – 35 mm	55 mm	61 mm	14 mm	59 to 72 mm	Blue	4	8161/8-M50-3516	239168	107 g
M63	28 – 48 mm	68 mm	75 mm	15 mm	64 to 78 mm	Blue	1	8161/8-M63-4828	239169	155 g
Product description Ambient temperature Variant Ex version			Cable gland With reduction sealing insert 15 °C ... +65 °C Long thread Ex e							
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M12	1 – 6 mm	16 mm	18 mm	15 mm	35 to 40 mm	Black	50	8161/7-M12-0601-L	239186	7 g
Product description Ambient temperature Variant Ex version			Cable gland With reduction sealing insert 15 °C ... +65 °C Long thread Ex i							
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M12	1 – 6 mm	16 mm	18 mm	15 mm	35 to 40 mm	Blue	50	8161/8-M12-0601-L	239194	7 g
Product description Ambient temperature Variant Ex version			Cable gland With reduction sealing insert 15 °C ... +65 °C Standard thread Ex e							
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M12	1 – 6 mm	16 mm	18 mm	9 mm	29 to 34 mm	Black	50	8161/7-M12-0601	239154	7 g
Product description Ambient temperature Variant Ex version			Cable gland With reduction sealing insert 15 °C ... +65 °C Standard thread Ex i							
Thread size	Clamping range	Width across flats	Width across corners	Thread length	Total length	Colour	Lot size	Product Type	Art. No.	Weight
M12	1 – 6 mm	16 mm	18 mm	9 mm	29 to 34 mm	Blue	50	8161/8-M12-0601	239162	7 g
Lot size: Purchase order quantity in [no. of units]; the delivery quantity is automatically rounded to the lot size.										

Technical Data		
Variant	8161/-M...-....	8161/-M...-....-LT
Explosion Protection		
IECEx gas explosion protection	Ex eb IIC Gb	Ex eb IIC Gb
IECEx dust explosion protection	Ex tb IIIC Db	Ex tb IIIC Db
ATEX gas explosion protection	Ⓔ II 2 G Ex eb IIC Gb	Ⓔ II 2 G Ex tb IIC Gb
ATEX dust explosion protection	Ⓔ II 2 D Ex tb IIIC Db	Ⓔ II 2 D Ex tb IIIC Db




Technical Data

Variant	8161/-M...-....	8161/-M...-....-LT
Explosion Protection		
Certificates	ATEX (PTB), Brazil (ULB), China (NEPSI), IECEx (PTB), Korea (KGS)	ATEX (PTB), Brazil (ULB), China (NEPSI), IECEx (PTB), Korea (KGS)
Declaration of conformity	ATEX (EUK), China (CCC)	ATEX (EUK), China (CCC)
Mechanical Data		
Material	Polyamide	Polyamide
Material	Polyamide, Glass fibre reinforced	Polyamide, Glass fibre reinforced
Degree of protection (IP)	IP66	IP66
Degree of protection note	IP68 at 5 bar 30 min. (IP protection according to IEC/EN 60529)	IP68 at 5 bar 30 min. (IP protection according to IEC/EN 60529)
Sealing material	EPDM profile seal	SI profile seal
Silicone-free	Yes	No
Self-extinguishing	Yes	Yes
Flame-retardant	Yes	Yes
Halogen-free	Yes	Yes
Surface resistance	$\leq 10^{13} \Omega$	$\leq 10^{13} \Omega$

Accessories

Figure	Description	Art. No.	Weight
Jam nut, nickel-plated brass			
	Material: Nickel-plated brass Thread size: M12 Lot size: 100	241518	220 g
	Material: Nickel-plated brass Thread size: M16 Lot size: 100	241519	290 g
	Material: Nickel-plated brass Thread size: M20 Lot size: 100	241520	480 g
	Material: Nickel-plated brass Thread size: M25 Lot size: 100	241561	720 g
	Material: Nickel-plated brass Thread size: M32 Lot size: 50	241562	545 g
	Material: Nickel-plated brass Thread size: M40 Lot size: 50	241563	1.03 kg
	Material: Nickel-plated brass Thread size: M50 Lot size: 25	241564	680 g
	Material: Nickel-plated brass Thread size: M63 Lot size: 10	241565	499 g
Jam nut, plastic (-40 to +75 °C) For mounting the cable entries in through holes			
	Material: Polyamide Thread size: M12 Lot size: 100	239460	1 g
	Material: Polyamide Thread size: M16 Lot size: 100	239461	2 g
	Material: Polyamide Thread size: M20 Lot size: 100	239462	2 g
	Material: Polyamide Thread size: M25 Lot size: 100	239463	3 g
	Material: Polyamide Thread size: M40 Lot size: 50	239465	7 g
	Material: Polyamide Thread size: M50 Lot size: 25	239466	12 g
	Material: Polyamide Thread size: M63 Lot size: 10	239467	18 g

Accessories

Figure	Description	Art. No.	Weight
Reduction sealing insert (standard), EPDM (-40 to +75 °C) For cable glands			
	Connection thread: M16 x 1.5 Clamping range: 2 to 6 mm	Batch size: 50	239445 1 g
	Connection thread: M20 x 1.5 Clamping range: 4 to 8 mm	Batch size: 50	239446 1 g
	Connection thread: M25 x 1.5 Clamping range: 7 to 12 mm	Batch size: 25	239447 2 g
	Connection thread: M32 x 1.5 Clamping range: 9 to 14 mm	Batch size: 25	239448 3 g
	Connection thread: M40 x 1.5 Clamping range: 12 to 20 mm	Batch size: 10	239449 7 g
Reduction sealing insert, silicone (-60 to +75 °C) For low temperatures			
	Connection thread: M16 x 1.5 Cable dia. range: 2 to 6 mm	Lot size: 50	239453 1 g
	Connection thread: M20 x 1.5 Cable dia. range: 4 to 8 mm	Lot size: 50	239454 1 g
	Connection thread: M25 x 1.5 Cable dia. range: 7 to 12 mm	Lot size: 25	239455 2 g
	Connection thread: M32 x 1.5 Cable dia. range: 9 to 14 mm	Lot size: 25	239456 3 g
	Connection thread: M40 x 1.5 Cable dia. range: 12 to 20 mm	Lot size: 10	239457 8 g
	Connection thread: M50 x 1.5 Cable dia. range: 16 to 25 mm	Lot size: 10	239458 15 g
Special key			
	Thread size: M20	Packaging unit: 1	114208 132 g
	Thread size: M25	Packaging unit: 1	114205 163 g
Special key For tightening cable glands and cap nuts			
	Thread size: M16	Packaging unit: 1	114207 120 g
	Thread size: M32	Packaging unit: 1	114209 237 g
	Thread size: M40	Packaging unit: 1	114210 274 g
Plug (-60 to +75 °C; depending on the cable gland used) For sealing unused cable glands Material: Polyamide			
	Diameter: 3 mm	Lot size: 50	240044 0 g
	Diameter: 6 mm	Lot size: 50	240046 0 g
	Diameter: 8 mm	Lot size: 50	240048 1 g
	Diameter: 12 mm	Lot size: 50	240049 2 g
	Diameter: 17 mm	Lot size: 50	240056 3 g
	Diameter: 14 mm	Lot size: 50	240050 3 g
	Diameter: 20 mm	Lot size: 25	240057 4 g
	Diameter: 28 mm	Lot size: 25	240059 9 g
	Diameter: 25 mm	Lot size: 25	240058 7 g
	Diameter: 35 mm	Lot size: 10	240060 10 g
	Diameter: 48 mm	Lot size: 10	240062 28 g


Spare Parts

Figure	Description		Art. No.	Weight
Flat seal (standard), EPDM (-40 to +75 °C)				
Replacement seals for cable glands				
	For cable glands 8161/-M12-06... Connection thread: M12 x 1.5	Lot size: 100	240245	0 g
	For cable glands 8161/-M12-06.. Connection thread: M12 x 1.5	Lot size: 50	240244	0 g
	For cable glands 8161/-M16-09.. Connection thread: M16	Lot size: 100	222370	0 g
	For cable glands 8161/-M16-09... Connection thread: M16	Lot size: 50	222363	0 g
	For cable glands 8161/-M20-13 Connection thread: M20	Lot size: 100	222371	1 g
	For cable glands 8161/-M20-13 Connection thread: M20	Lot size: 50	222364	1 g
	For cable glands 8161/-M25-17 Connection thread: M25	Lot size: 100	222372	1 g
	For cable glands 8161/-M25-17 Connection thread: M25	Lot size: 50	222365	1 g
	For cable glands 8161/-M32-21 Connection thread: M32	Lot size: 100	222373	1 g
	For cable glands 8161/-M32-21 Connection thread: M32	Lot size: 50	222366	0 g
	For cable glands 8161/-M40-28 Connection thread: M40	Lot size: 100	222374	2 g
	For cable glands 8161/-M40-28 Connection thread: M40	Lot size: 50	222367	2 g
	For cable glands 8161/-M50-35 Connection thread: M50	Lot size: 100	222375	2 g
	For cable glands 8161/-M50-35 Connection thread: M50	Lot size: 50	222368	2 g
	For cable glands 8161/-M63-48 Connection thread: M63	Lot size: 100	222376	2 g
	For cable glands 8161/-M63-48 Connection thread: M63	Lot size: 50	222369	2 g
Silicone flat seal (-60 to +75 °C)				
Replacement seals for low temperatures				
	For cable glands 8161/-M16-09.. Connection thread: M16	Lot size: 100	240248	0 g
	For cable glands 8161/-M20-13 Connection thread: M20	Lot size: 100	240249	1 g
	For cable glands 8161/-M25-17 Connection thread: M25	Lot size: 100	240250	1 g
	For cable glands 8161/-M32-21 Connection thread: M32	Lot size: 100	240251	1 g
	For cable glands 8161/-M40-28 Connection thread: M40	Lot size: 100	240252	2 g
	For cable glands 8161/-M50-35 Connection thread: M50	Lot size: 100	240253	2 g
	For cable glands 8161/-M63-48 Connection thread: M63	Lot size: 100	240254	2 g

Lot size: Purchase order quantity in [no. of units]; the delivery quantity is automatically rounded to the lot size.

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations

E10



M = Thread size SW = Width across flats
L1 = Thread length L = Total length

Cable glands without bend protection

Thread size	Width across flats	Total length	Total length (with long thread)	Thread length	Thread length (long thread)	Clamping range + reduction sealing insert	Dimension d1	Dimension d2	Dimension d4
M12	16.00 mm	29 to 34 mm	35 to 40 mm	9 mm	15 mm	1 - 6 mm	18 mm	7.3 mm	6.3 mm
M16	20.00 mm	31 to 37 mm	37 to 43 mm	9 mm	15 mm	2 - 9 mm	22 mm	10.3 mm	9.3 mm
M20	24.00 mm	36 to 43 mm	41 to 48 mm	10 mm	15 mm	4 - 13 mm	27 mm	13.3 mm	13.3 mm
M25	29.00 mm	38 to 46 mm	43 to 51 mm	10 mm	15 mm	7 - 17 mm	32 mm	17.3 mm	17.3 mm
M32	36.00 mm	42 to 50 mm	45 to 53 mm	12 mm	15 mm	9 - 21 mm	40 mm	21.3 mm	21.3 mm
M40	46.00 mm	52 to 65 mm	58 to 71 mm	12 mm	18 mm	12 - 28 mm	51 mm	28.3 mm	30 mm
M50	55.00 mm	59 to 72 mm	63 to 76 mm	14 mm	18 mm	16 - 35 mm	61 mm	35.3 mm	40 mm
M63	68.00 mm	64 to 78 mm	67 to 81 mm	15 mm	18 mm	28 - 48 mm	75 mm	48.3 mm	53 mm