

A Higher Level of Performance



Data Sheet

Senator H80I Radar Series

Level Measurement



For more information, please visit >
www.hawkmeasurement.com



Overview

Senator H80I Radar Series



Overview

Offering a unique blend of compact design and efficiency, the Senator H80I is a 80GHz FMCW radar level transmitter ideal for continuous level measurement of liquids, slurries and solids. It guarantees value without compromising quality and ease of operation. With its flexible mounting options, high chemical compatibility, and a 120m (393.7ft) measuring range, the Senator H80I is versatile enough to meet the demands of diverse industrial applications. Simple commissioning available by multiple convenient methods including keypad, HawkBTConnect bluetooth App, Goshawk PC software & the HRC HART Remote Configurator.


Principle of Operation

The Senator H80I transmits a radar pulse at the speed of light, bouncing off the surface of the measured material. Proprietary software then analyzes the returned signal, enhancing the accurate reflection while eliminating any false ones.

Primary Areas of Application

- Chemicals
- Petrochemicals
- Cement
- Building Aggregates
- Mining / Minerals
- Food & Beverages
- Oil & Gas
- Pharmaceutical
- Pulp & Paper
- Wastewater

Simple Commissioning via Keypad, HawkBTConnect Bluetooth App & Goshawk Software & HRC HAWK HART Configurator



Features


- 80GHz FMCW Radar
- 4-20mA HART, Modbus output options
- Full commissioning via Keypad & Display, HawkBTConnect Bluetooth App, Goshawk PC software & HRC HART Remote Configurator
- Maximum range to 120m (393.7ft)
- Non-contact measurement
- Low cost per measuring point
- Ingress protection class IP67
- Variety of mounting options

Mounting, Dimensions, Wiring


Senator H80I Radar Series



Mounting





Wiring




Dimensions

Integral - 3.5" / Aiming Flange version



The adjustable flanged requires a 3/16" Allen key
Air purge fitting: PC6-M5 push to connect. 6mm tubing.

Integral - 3.5" Threaded version




Dimensions


Senator H80I Radar Series




Integral - 2" Threaded version




Integral - 1.5" Threaded version



Integral - 1.5" Tri-Clamp Version



Integral - 1" Threaded version





Part Numbering

3.5" / Aiming Flange Version for Liquids Applications

Note: Unit should be purchased with Flange (3.5" fittings are uncommon)

Model

H80I Hawk Radar 80GHz Integral Version, Bluetooth

Application

L Liquids

Maximum Range

65 65m (213.2ft)

Output

H 4-20mA HART, Modbus

Housing

A Powder Coated Aluminium

Cable Entries

M 2 x M20

Mounting

AF35 DN100 PN16 Aiming Flange with Air Purge

FFFF Flange¹

TB35 3.5" BSP / G3

TN35 3.5" NPT

Antenna / Mounting Material

C 316

P 316 Antenna & Flange with PTFE Seal¹

T 316 Antenna & 304 Flange with PTFE Seal¹

Temperature

1 -40 to +80°C (-40 to +176°F)

Pressure

1 3 Bar (43 psig)

2 16 Bar (232 psig)²

Approval

XX Not required

H80I L 65 H A M AF35 C 1 1 XX

¹ See Flange Part Selection

² Antenna / Mounting option P, T only



Part Numbering

3.5" / Aiming Flange Version for Solids Applications

Note: Unit should be purchased with Flange (3.5" fittings are uncommon)

Model

H80I Hawk Radar 80GHz Integral Version, Bluetooth

Application

S Solids

Maximum Range

30 30m (98.4ft)

Output

H 4-20mA HART, Modbus

Housing

A Powder Coated Aluminium

Cable Entries

M 2 x M20

Mounting

AF35 DN100 PN16 Aiming Flange with Air Purge

FFFF Flange¹

TB35 3.5" BSP / G3

TN35 3.5" NPT

Antenna / Mounting Material

C 316

P 316 Antenna & Flange with PTFE Seal¹

T 316 Antenna & 304 Flange with PTFE Seal¹

Temperature

1 -40 to +80°C (-40 to +176°F)

Pressure

1 3 Bar (43 psig)

2 16 Bar (232 psig)²

Approval

XX Not required

H80I S 30 H A M AF35 C 1 1 XX

¹ See Flange Part Selection

² Antenna / Mounting option P, T only



Part Numbering

2" Threaded Version for Liquids Applications

Model

H80I Hawk Radar 80GHz Integral Version, Bluetooth

Application

L Liquids

Maximum Range

10 10m (32.8ft)
20 20m (65.6ft)
30 30m (98.4ft)
65 65m (213.2ft)

Output

H 4-20mA HART, Modbus

Housing

A Powder Coated Aluminium

Cable Entries

M 2 x M20

Mounting

TB20 2" BSP / G2

TN20 2" NPT

FFFF Flange¹

Antenna / Mounting Material

C 316

P 316 Antenna & Flange with PTFE Seal¹

T 316 Antenna & 304 Flange with PTFE Seal¹

Temperature

1 -40 to +80°C (-40 to +176°F)

2 -29 to +150°C (-20 to +302°F)

3 0 to +260°C (+32 to 500°F)

Pressure

1 3 Bar (43 psig)

2 16 Bar (232 psig)²

Approval

XX Not required

H80I L 20 H A M TN20 C 1 1 XX

¹ See Flange Part Selection

² Antenna / Mounting option P, T only



Part Numbering

2" Threaded Version for Solids Applications

Model

H80I Hawk Radar 80GHz Integral Version, Bluetooth

Application

S Solids

Maximum Range

10 10m (32.8ft)

20 20m (65.6ft)

30 30m (98.4ft)

Output

H 4-20mA HART, Modbus

Housing

A Powder Coated Aluminium

Cable Entries

M 2 x M20

Mounting

TB20 2" BSP / G2

TN20 2" NPT

FFFF Flange¹

Antenna / Mounting Material

C 316

P 316 Antenna & Flange with PTFE Seal¹

T 316 Antenna & 304 Flange with PTFE Seal¹

Temperature

1 -40 to +80°C (-40 to +176°F)

2 -29 to +150°C (-20 to +302°F)

3 0 to +260°C (+32 to 500°F)

Pressure

1 3 Bar (43 psig)

2 16 Bar (232 psig)²

Approval

XX Not required

H80I S 20 H A M TN20 C 1 1 XX

¹ See Flange Part Selection

² Antenna / Mounting option P, T only



Part Numbering

1.5" Threaded Version for Liquids Applications

Model

H80I Hawk Radar 80GHz Integral Version, Bluetooth

Application

L Liquids

Maximum Range

10 10m (32.8ft)

20 20m (65.6ft)

30 30m (98.4ft)

Output

H 4-20mA HART, Modbus

Housing

A Powder Coated Aluminium

Cable Entries

M 2 x M20

Mounting

TB15 1.5" BSP / G1.5

TN15 1.5" NPT

FFFF Flange¹

Antenna / Mounting Material

C 316

P 316 Antenna & Flange with PTFE Seal¹

T 316 Antenna & 304 Flange with PTFE Seal¹

Temperature

1 -40 to +80°C (-40 to +176°F)

Pressure

1 3 Bar (43 psig)

2 16 Bar (232 psig)²

Approval

XX Not required

H80I L 20 H A M TB15 C 1 1 XX

¹ See Flange Part Selection

² Antenna / Mounting option P, T only



Part Numbering

1.5" Threaded Version for Solids Applications

Model

H80I Hawk Radar 80GHz Integral Version, Bluetooth

Application

S Solids

Maximum Range

10 10m (32.8ft)

20 20m (65.6ft)

Output

H 4-20mA HART, Modbus

Housing

A Powder Coated Aluminium

Cable Entries

M 2 x M20

Mounting

TB15 1.5" BSP / G1.5

TN15 1.5" NPT

FFFF Flange¹

Antenna / Mounting Material

C 316

P 316 Antenna & Flange with PTFE Seal¹

T 316 Antenna & 304 Flange with PTFE Seal¹

Temperature

1 -40 to +80°C (-40 to +176°F)

Pressure

1 3 Bar (43 psig)

2 16 Bar (232 psig)²

Approval

XX Not required

H80I S 10 H A M TB15 C 1 1 XX

¹ See Flange Part Selection

² Antenna / Mounting option P, T only

Part Numbering

Senator H80I Radar Series



Part Numbering

1" Threaded Version for Liquids Applications

Model

H80I 80GHz Integral, Bluetooth

Application

L Liquids

Maximum Range

10 10m (32.8ft)

Output

H 4-20mA HART, Modbus

Housing

A Powder Coated Aluminium

Cable Entries

M 2 x M20

Mounting

TB10 1" BSP / G1

TN10 1" NPT

FFFF Flange¹

Antenna / Mounting Material

C 316

P 316 Antenna & Flange with PTFE Seal¹

T 316 Antenna & 304 Flange with PTFE Seal¹

Temperature

1 -40 to +80°C (-40 to +176°F)

Pressure

1 3 Bar (43 psig)

2 16 Bar (232 psig)²

Approval

XX Not required

H80I L 10 H A M TB10 C 1 1 XX

¹ See Flange Part Selection

² Antenna / Mounting option P, T only

Part Numbering

Senator H80I Radar Series



Part Numbering

1" Threaded Version for Solids Applications

(1" version not recommended for solids unless necessary / simple application)

Model

H80I 80GHz Integral, Bluetooth

Application

S Solids

Maximum Range

10 10m (32.8ft)

Output

H 4-20mA HART, Modbus

Housing

A Powder Coated Aluminium

Cable Entries

M 2 x M20

Mounting

TB10 1" BSP / G1

TN10 1" NPT

FFFF Flange¹

Antenna / Mounting Material

C 316

P 316 Antenna & Flange with PTFE Seal¹

T 316 Antenna & 304 Flange with PTFE Seal¹

Temperature

1 -40 to +80°C (-40 to +176°F)

Pressure

1 3 Bar (43 psig)

2 16 Bar (232 psig)²

Approval

XX Not required

H80I S 10 H A M TB10 S 1 1 XX

¹ See Flange Part Selection

² Antenna / Mounting option P, T only

Part Numbering

Senator H80I Radar Series



Mounting Flanges

Flange Selection (replaces FFFF 4 Digit Mounting Option)

Thread Type

- 1 1" G/BSP
- A 1.5" G/BSP
- 2 2" G/BSP
- B 3.5" G/BSP
- 5 1" NPT
- C 1.5" NPT
- 7 2" NPT
- 8 3.5" NPT

Flange Size (must be suitable to fit thread size)

- 1 1" or DN25 or 25mm
- 2 2" or DN50 or 50mm
- 3 3" or DN80 or 80mm
- 4 4" or DN100 or 100mm
- 5 5" or DN125 or 125mm
- 6 6" or DN150 or 150mm

Flange Type

- A1 ANSI B16.5 150LB
- A3 ANSI B16.5 300LB
- D1 EN 1092-1 PN16
- D2 EN 1092-1 PN25
- C1 HG/T 20592 PN16
- C2 HG/T 20592 PN25

7 4 A1

Specifications

Senator H80I Radar Series



Frequency

- 80GHz FMCW

Operating Voltage

- 17 - 36VDC

Communications

- Modbus
- HART 7
- PC Software (Goshawk)
- iOS & Android HawkBTConnect App (via bluetooth)

Keypad / Display

- 4 button, 128 x 64 backlit LCD

Blanking Distance

- 150 mm (6")

Maximum Range

- Integral: Up to 120m (393.7ft), model dependant
- Compact: Up to 30m (98ft)

Resolution

- 1mm (0.04")

Accuracy

- +/- 2mm (0.08")

LCD Response Time

- 1 second

Sample Rate

- 3 seconds

Startup Time

- Approx. 50 seconds

Memory

- Non-volatile

Operating Temperature

- -40°C to +80°C (-40°F to +176°F)
- -29°C to +150°C (-20°F to +302°F)
- 0°C to +260°C (+32°F to 500°F)

Operating Pressure

- 3 Bar (43 psig)
- 16 Bar (232 psig)

Beam Angle

- 1" Antenna: 8°
- 1.5" Antenna: 7°
- 2" Antenna: 5.8°
- 3.5" Antenna: 3.8°

Enclosure Material

- Powder Coated Aluminium

Antenna / Mounting Material

- 316 SS Antenna
- 304 / 316 / PTFE Sealed Flange

Sensor Face Material

- PTFE
- PFA (high temperature version)

Enclosure Sealing

- IP67

Cable Entries

- 2 x M20

Mounting

- 1", 1.5", 2", 3.5" Threaded (NPT, G/BSP)
- Flanged

Air Purge

- PC6-M5 Push-to-Connect Fitting
- Intermittent Mode: Max. 6 bar
- Continuous Mode: Max. 1 bar

Typical Weight

- 2kg (4.4lb)

Hawk Measurement Systems (Head Office)

15 - 17 Maurice Court
Nunawading VIC 3131, AUSTRALIA
Phone: +61 3 9873 4750
Fax: +61 3 9873 4538
info@hawk.com.au

For more information and global representatives: www.hawkmeasurement.com

Additional product warranty and application guarantees upon request.
Technical data subject to change without notice.

Hawk Measurement

5010 Gateway Drive, Medina, OH 44256, USA
Phone: +1 888 HAWKLEVEL (1-888-429-5538)
Phone: +1 978 304 3000 / +1 877-356-5463
Fax: +1 978 304 1462 / +1 330-331-7172
info@hawkmeasurement.com

Represented by:

